


21.447.20
2-Wege Kugelhahn VK Dual Block aus PVC-U mit integrierter Halterung, ohne Gewindebuchsen, radial lösbar


Mit gesicherten Überwurfmutter.
 Austauschbare Gewinde und identische Einbaulängen wie Kugelhahn VK.
 Anschluß: Klebemuffen.
 Dichtwerkstoff: PTFE/EPDM.

VKDIV/EPDM

DN	de	Art.-Nr.	PN	B	B ₁	C	C ₁	E	H	H ₁	L	Z	kg	LS	VE
10	16	121.447.020.016	16	54,0	29,0	67	27	54	103	65	14	75	0,215	1	22
15	20	121.447.020.020	16	54,0	29,0	67	27	54	103	65	16	71	0,205	1	22
20	25	121.447.020.025	16	65,0	34,5	85	36	65	115	70	19	77	0,330	1	12
25	32	121.447.020.032	16	69,5	39,0	85	36	73	128	78	22	84	0,438	1	12
32	40	121.447.020.040	16	82,5	46,0	108	44	86	146	88	26	94	0,693	1	8
40	50	121.447.020.050	16	89,0	52,0	108	44	98	164	93	31	102	0,925	1	8
50	63	121.447.020.063	16	108,0	62,0	134	58	122	199	111	38	123	1,577	1	8

21.447.20
2-Wege Kugelhahn VK Dual Block aus PVC-U mit integrierter Halterung, ohne Gewindebuchsen, radial lösbar


Mit gesicherten Überwurfmutter.
 Anschluß: Klebemuffen.
 Dichtwerkstoff: PTFE/EPDM.

VKDIV/EPDM

DN	de	Art.-Nr.	PN	B	B ₁	C	C ₁	E	H	H ₁	Z	kg	LS	VE	€/St.	PG
65	75	121.447.020.075	16	164	87	327	272	164	235	133	147	4,380	1	1		
80	90	121.447.020.090	16	177	105	327	272	203	270	149	168	7,200	1	1		
100	110	121.447.020.110	16	195	129	385	330	238	308	167	186	11,141	1	1		